



Technical specification bucket

JET 44 P


Jokey Euro Tainer Profi



dimensions

D1: 227,0 mm
D2: 210,0 mm
D3: 195,0 mm
H:* 156,0 mm

*Height without lid



basic data	volume to rim:	4,90 l	handle types	metal handle	21,0 g	tolerances	dimensions:	+/- 1 mm
	weight:	115,0 g	plastic handle		8,5 g	volume/weight:		+/- 5 %
	weight group:	E	belt handle		-			
			no handle		-			
			body grip		-			
			roller grips		-			

decoration	Digital	IML	offset
height:	100,0 mm	134,53 mm	100,0 mm
width:	610,0 mm	645,66 mm	610,0 mm
median breadth:	626,0 mm		626,0 mm

lid	DET 225 P	FDET 225 P	FDET 225 P
	standard	sealing lid	sealing lid
stacking height two fold:	303,0 mm	0,0 mm	320,5 mm
each further:	147,0 mm	0,0 mm	157,0 mm

logistic Max. compression for standard lid at 20°C on the lowest pallet: 19,00 kg


pieces per pallet

bucket 1080
pallet height 2,20 m

layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.



Technical specification lid DET 225 P



dimensions

D1: 223,0 mm
H: 12,0 mm

basic data

displaced volume:: 0,30 l
weight: 33,0 g
weight group: D

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

194,00 mm

offset

182,0 mm

bucket




logistic

pieces per pallet

lid 5400
pallet height 2,20 m
layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid

FDET 225 P



dimensions

D1: 222,0 mm
H: 19,0 mm

basic data

displaced volume:: 0,00 l
weight: 28,0 g
weight group: C

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,00 mm

offset

0,0 mm

bucket




logistic

pieces per pallet

lid 4800
pallet height 2,20 m
layer quantities: 18

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0



Technical specification lid

FDET 225 P



dimensions

D1: 222,0 mm
H: 19,0 mm

basic data

displaced volume:: 0,00 l
weight: 35,0 g
weight group: F

tolerances

dimensions: +/- 1 mm
volume/weight: +/- 5 %

decoration

Diameter

IML

0,00 mm

offset

0,0 mm

bucket




logistic

pieces per pallet

lid 0
pallet height 0,00 m
layer quantities: 0

EUP (Europallet)

80 cm (31,5'') x 120 cm (47,24'')



material



QM / certificates

You can download our current certificates on www.jokey.com.

misc.

All deliveries are subject to our General Terms and Conditions of Delivery. With respect to possible tolerances, deformations and ink adhesion of the design, express reference is hereby made to our Technical Guidelines, which shall also form an integral part of the content of any delivery transaction. In our Technical Guidelines you will also find details referring to strictest quality and hygiene standards, storage, filling and performance requirements as well to applications and transport. Verbal statements regarding technical data or attributes of our products shall always be limited to the scope that we recommend. Our terms and Conditions of Delivery and Technical Guidelines may be available. For technical reasons, the product image may deviate from the actual item. Technical modifications reserved.

Please find further Information at www.jokey.com or via email info@jokey.com

Date: 07.12.2020 rev. 3.0